



# F SERIES

## FEATURES

### F SERIES F-10/F-12/F-15/F-215/S-18/S-218

#### PHYSICAL PROPERTIES

● **Product Type:** The **F Series** are different from the **FB Series** that features higher quality components. The **F-10**, **F-12**, **F-15** and **F-215** are wide-range compact loudspeakers system, two-way/two-speaker, high power, short throw with built-in passive filter. And the **S-18**, **S-218** are **SUB** bass loudspeakers system, high efficiency, high power system for the reproduction of low frequencies.

● **Enclosure Material and Finish:** Asymmetric enclosure in 15 or 18mm plywood and MDF with internal bracing, rounded corners, integral handles and rotating speaker baffle. Gray ultra thane paint.

● **Standard Accessories:** Steel grill, 2 handles internal support tube/stand housing; flying points with nut plates, Speakon NL4FC connector.

● **Connectors:** 2 X NL4 speakon in parallel  
LF and HF Pin 1+ 2+ pos; Pin 1- 2- neg

## DESCRIPTION

- Live club performance
- Bars, restaurants and theatres etc.
- Installed applications
- Special effects sub-bass



F-10



F-12



F-15



F-215

## TECHNICAL INFORMATION

Model	F-10	F-12	F-15	F-215
Power-Watts	300W (RMS)/750W(PGM)	400W (RMS)/1000W(PGM)	500W (RMS)/1250W(PGM)	1000W (RMS)/2500W(PGM)
Sensitivity(dBSPL)	97dB (1W/1M)	98dB (1W/1M)	99dB (1W/1M)	102dB (1W/1M)
Impedance (ohms)	8 Ω	8 Ω	8 Ω	4 Ω
Frequency Response	50Hz~19kHz	45Hz~20kHz	35Hz~20kHz	40Hz~20kHz
Average Dispersion	90° X 60°	90° X 60°	90° X 60°	90° X 60°
Loudspeaker and Loading	1 X 10"	1 X 12"	1 X 15"	2 X 15"
LF	High pass vented box	High pass vented box	High pass vented box	High pass vented box
HF	1 X 1"	1 X 1"	1 X 1.5"	1 X 1.5"
	Exit horn loaded	Exit horn loaded	Exit horn loaded	Exit horn loaded
Weight(Kg)	16.2Kg	19Kg	31.5Kg	53Kg
Dimensions (WxDxH)	355x315x500mm	405x367x573mm	475x443x690mm	556x496x1076mm
Packing (WxDxH)	430x390x580mm	485x450x655mm	555x525x770mm	636x576x1161mm