

PS 系统描述

系统特点:

PS SERIES

FEATURES

PS SERIE PS-8/PS-10/PS-12/PS-15/PS-15A/LS-500/FAR-18

PHYSICAL PROPERTIES

Product Type: The PS Series are Wide-range loudspeakers system, two-way/two-speaker, medium power, short throw with built-in passive filter.

Enclosure Material and Finish: Asymmetric enclosure in 15mm or 18mm plywood with internal bracing and rounded corners, useable in one horizontal position 45° . Black ultra thane paint.

Standard Accessories: Highly resistant vibration-free protective perforated steel grill covered in black foam; 2 handles internal support tube/stand housing; flying points with nut plates, Speakon NL4FC connector.

Connectors: 2×NL4 speakon in parallel
LF and HF Pin 1+2+pos; Pin 1-2-neg

DESCRIPTION

Live club performance

Stage monitoring for clubs, A/V, theater etc.

Installed applications

Model:PS-10

技术指标:

Power-Watts (功率)	300W(RMS)/750W(PGM)
Sensitivity(dBSPL 1W/1M) (灵敏度)	97dB(1W/1M)
Impedance (ohms) (阻抗)	8Ω
Frequency Response (频率响应)	45Hz~19KHz
Average Dispersion (指向性)	60° ×60°
Loudspeaker and loading (单元配置)	LF :1×10” High pass vented box HF: 1×1” Eixt horn loaded
Weigh(Kg) (重量)	15Kg
Dimensions (W×D×H) (体积)	316×277×515mm
Packing (W×D×H)	391×352×595mm