AQ SEFIES

DESCRIPTION

FQ SERIES AQ-10/AQ-12/AQ-15

PHYSICAL PROPERTIES

Product Type: The AQ Series are wide-range compact loudspeakers system, two-way /two-speaker, medium power, short throw with built-in passive filter.

Enclosure Material and Finish: Trapezoidal enclosure in 15mm MDF or plywood with internal bracing. Yellow white ultra thane paint.

Standard Accessories : Steel grill ,flying points with nut plates, Speakon NL4FC connector.

Connectors: 2 X NL4 speakon in parallel LF and HF Pin 1+,2+ pos; Pin 1-,2- neg

Technical Information

Model AQ-10

Power rating 150W(RMS) Sensitivity(1W/1M) 96db Impedance(ohms) 8Ω

Frequency Response(-3db) 50Hz~19KHz

Average Dispersion 90 \times 60

Loudspeaker and Loading LF:1 \times 10"High pass vented box

HF:1×1" Exit hom loaded

Weight 18kg

Dimension(W \times D \times H) 316 \times 325 \times 504mm Packing (W \times D \times H) 385 \times 400 \times 585mm

Model AQ-12

 $\begin{array}{ll} \mbox{Power rating} & 350\mbox{W(RMS)} \\ \mbox{Sensitivity}(1\mbox{W}/1\mbox{M}) & 97\mbox{db} \\ \mbox{Impedance(ohms)} & 8\Omega \end{array}$

Frequency Response(-3db) 45Hz~19KHz

Average Dispersion $90^{\circ} \times 60^{\circ}$

Loudspeaker and Loading LF:1 × 12"High pass vented box

HF:1×1" Exit hom loaded

Weight 19.5kg

Dimension(W \times D \times H) 360 \times 365 \times 561mm Packing (W \times D \times H) 445 \times 440 \times 640mm

Model AQ-15

Power rating 450W(RMS)

 $\begin{array}{ll} \mbox{Sensitivity(1W/1M)} & \mbox{99db} \\ \mbox{Impedance(ohms)} & \mbox{8} \Omega \end{array}$

Frequency Response(-3db) 45Hz~19KHz

Average Dispersion $90^{\circ} \times 60^{\circ}$

Loudspeaker and Loading LF:1×15"High pass vented box

HF:1×1.5" Exit hom loaded

Weight 36kg

 $\begin{array}{ll} \text{Dimension(W} \times \text{D} \times \text{H}) & 435 \times 435 \times 706 \text{mm} \\ \text{Packing (W} \times \text{D} \times \text{H}) & 515 \times 515 \times 786 \text{mm} \end{array}$