



PS SERIES

FEATURES

PS SERIES PS-8/PS-10/PS-12/PS-15/PS-15A

PHYSICAL PROPERTIES

- Product Type: The PS Series are Wide-range loudspeakers system, two-way /two-speaker, medium power, short throw with built-in passive filter.
- Enclosure Material and Finish: Asymmetric enclosure in 15mm or 18mm plywood with internal bracing, and rounded corners, useable in one horizontal position 45°. Black ultra thane paint.
- Standard Accessories: Highly resistant vibration-free protective perforated steel grill covered in black foam; 2 handles internal support tube/stand housing; flying points with nut plates, Speakon NL4FC connector.
- ●Connectors:2 X NL4 speakon in parallel LF and HF Pin 1+,2+ pos;Pin 1-,2- neg

DESCRIPTION

- ●Live club performance
- Stage monitoring for clubs, A/V, theater etc.
- Installed applications











PS-8

PS-10

PS-12

PS-15

PS-15A

Model	PS-8	PS-10	PS-12	PS-15	PS-15A
Power-Watts	200W (RMS)/500W(PGM)	300W (RMS)/750W(PGM)	350W (RMS)/875W(PGM)	400W (RMS)/1000W(PGM)	450W (RMS)/1125W(PGM)
Sensitivity(dBSPL)	96dB (1W/1M)	97dB (1W/1M)	98dB (1W/1M)	99dB (1W/1M)	100dB (1W/1M)
mpedance (ohms)	8Ω	8Ω	8Ω	8 Ω	8Ω
Frequency Response	55Hz~19kHz	50Hz~19kHz	50Hz~20kHz	55Hz~20kHz	45Hz~20kHz
Average Dispersion	60° X 60°	60° X 60°	60° X 60°	60° X 60°	60° X 60°
Loudspeaker and Load	ling				
LF	1 X 8"High pass vented box	1 X 10" High pass vented box	9	1 X 15"High pass vented box	1 X 15"High pass vented box
HF	1 X 1"	1 X 1"	1 X 1"	1 X 1"	1 X 2"
	Exit horn loaded	Exit horn loaded	Exit horn loaded	Exit horn loaded	Exit horn loaded
Weight(Kg)	8.5Kg	15Kg	17.5Kg	25Kg	35Kg
Dimensions (WxDxH)	252x214x430mm	316x277x515mm	351x306x570mm	443x368x690mm	443x368x690mm
Packing (WxDxH)	321x280x490mm	391x352x595mm	430x381x650mm	521x443x770mm	521x443x770mm