PS 系统描述

系统特点:

PS SERIES

FEATURES

PS SERIE PS-8/PS-10/PS-12/PS-15/PS-15A/LS-500/FAR-18

PHYSICAL PROPERTIES

Product Type: The **PS Series** are Wide-range loudspeakers system,

two-way/two-speaker, medium power, short throw with built-in passive filter.

Enclosure Material and Finish: Asymmetric enclosure in 15mmor 18mm plywood with internal bracing and rounded corners, useable in one horizontal position 45° . Black ultra thane paint.

Standard Accessories: Highly resistant vibration-free protective perforated steel grill covered in black foam;2 handles internal support tube/stand housing; flying points with nut plates, Speakon NL4FC connector.

Connectors: 2×NL4 speakon in parallel LF and HF Pin 1+2+pos;Pin 1-2-neg

DESCRIPTION

Live club performance Stage monitoring for clubs, A/V, theater etc. Installed applications

Model:PS-8

技术指标:

Power-Watts(功率) 200W(RMS)/500W(PGM)

Sensitivity(dBSPL 1W/1M)(灵敏度) 96dB(1W/1M)

Impedance (ohms) (阻抗) 8 Ω

Frequency Response(频率响应) 55Hz~19KHz Average Dispersion(指向性) 60°×60°

Loudspeaker and loading(单元配置) LF:1×8" High pass vented box

HF: 1×1" Eixt horn loaded

Weigh(Kg) (重量)

Dimensions (W×D×H)(体积)

Packing (W \times D \times H)

8.5Kg 252×214×430mm

 $321 \times 280 \times 490$ mm