TOURING INSTALLATION SYSTEM







DESCRIPTION

FQ SERIES AQ-10/AQ-12/AQ-15

PHYSICAL PROPERTIES

- Product Type: The AQ Series are wide-range compact loudspeakers system, two-way /two-speaker, medium power, short throw with built-in passive filter.
- Enclosure Material and Finish: Trapezoidal enclosure in 15mm MDF or plywood with internal bracing. Yellow white ultra thane paint.
- Standard Accessories: Steel grill, flying points with nut plates, Speakon NL4FC connector.
- Connectors:2 X NL4 speakon in parallel LF and HF Pin 1+,2+ pos;Pin 1-,2- neg

APPLICATION

- Live club performance
- Bars, restaurants and theatres etc.
- Installed applications







AQ-12



AQ-15

SPECIFICATIONS	AQ-10	AQ-12	AQ-15
Power-Watts	150W (RMS)	350W (RMS)	450W (RMS)
Sensitivity(dBSPL 1W/1M)	96dB (1W/1M)	97dB (1W/1M)	99dB (1W/1M)
Impedance (ohms)	8 Ω	8 Ω	8 Ω
Frequency Response	50Hz~19kHz	45Hz~19kHz	45Hz~19kHz
Average Dispersion	90° X 60°	90° X 60°	90° X 60°
Loudspeaker and Loading			
LF	1 X 10 " High pass	1 X 12 " High pass	1 X 15 " High pass
	vented box	vented box	vented box
HF	1 X 1 " Exit horn loaded	1 X 1 " Exit horn loaded	1 X 1.5 " Exit horn loaded
Weight(Kg)	18Kg	19.5Kg	36Kg
Dimensions (WxDxH)	316x325x504mm	360x365x561mm	435x435x706mm
Packing (WxDxH)	385x400x585mm	445x440x640mm	515x515x786mm