



F SERIES

FEATURES

F SERIES F-10/F-12/F-15/F-215/S-18/S-218

PHYSICAL PROPERTIES

- **Product Type:** The **F Series** are different from the **FB Series** that features higher quality components. The **F-10**, **F-12**, **F-15** and **F-215** are wide-range compact loudspeakers system, two-way/two-speaker, high power, short throw with built-in passive filter. And the **S-18**, **S-218** are **SUB** bass loudspeakers system, high efficiency, high power system for the reproduction of low frequencies.
- **Enclosure Material and Finish:** Asymmetric enclosure in 15 or 18mm plywood and MDF with internal bracing, rounded corners, integral handles and rotating speaker baffle. Gray ultra thane paint.
- **Standard Accessories:** Steel grill, 2 handles internal support tube/stand housing; flying points with nut plates, Speakon NL4FC connector.
- **Connectors:** 2 X NL4 speakon in parallel
LF and HF Pin 1+ 2+ pos; Pin 1- 2- neg

DESCRIPTION

- Live club performance
- Bars, restaurants and theatres etc.
- Installed applications
- Special effects sub-bass



S-18

S-218

TECHNICAL INFORMATION

Model	S-18	S-218
Power-Watts	600W (RMS)/1500W(PGM)	1200W (RMS)/3000W(PGM)
Sensitivity(dBSPL 1W/1M)	98dB (1W/1M)	101dB (1W/1M)
Impedance (ohms)	8Ω	4Ω
Frequency Response	50Hz~190Hz	35Hz~140Hz
Loudspeaker and Loading	Quasi-omnidirectional	Quasi-omnidirectional
LF	1 X 18"	2 X 18"
HF	High pass vented box	High pass vented box
Weight(Kg)	/	/
Weight(Kg)	41Kg	88Kg
Dimensions (WxDxH)	561x595x690mm	1066x780x561mm
Packing (WxDxH)	661x695x790mm	1166x880x661mm